



SMARTWELD JET

AUTOMATE THE PREHEATING PROCESS FOR YOUR ORIGINAL THERMIT® WELD

The Smartweld Jet preheating device from Goldschmidt guarantees the reliable and reproducible execution of the preheating process, ensuring consistently high quality Original Thermit® welds. This device makes your work processes both easier and safer. With automatisation and simplified operation prevents execution errors that are costly to rectify.

TECHNICAL DATA

SPECIFICATIONS

Dimensions (L x W x H)	1011 x 481 x 509 mm
Weight	23 kg
Output	Max. 150 kW
Flame temperature	> 1000 °C
Propane gas pressure	20 kPa

CERTIFICATIONS/APPROVALS

Certified for Thermit® welding processes SoW-5, SkV-Elite L25 to EN 14730

Certified for Thermit® welding process SRZ to EN 16771

Approved by railway companies in Europe and Russia

BENEFITS

- Simplifies the preheating process for the welder by controlling the welding parameters and automatically igniting and monitoring the flame
- Reduces the effort for transport and logistics through eliminating the need for compressed oxygen and by providing the option of using small propane gas cylinders
- Optimising the preheating process protects the moulds thanks to lower temperatures and uniform heat input

CONTENTS

- · Smartweld Jet including nozzle
- Gas hose with quick-release connector and pressure drop shut-off device
- Pressure regulator with Euro adapter set
- · Power connection cable

ACCESSORIES

- Clamping device
- · Setting gauge
- Transport and storage box
- Gas leakage shut-off device for propane





